


Electrical Characteristics :
 Insulation Resistance : 500MΩ Min.
 Contact Resistance : 30mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 CUL File No : E215573

PART NO : 3 2 8 8 - B * 1

Positions →
 Contacts →
 Ports →
 Gold Plated
 1 : 8u"
 2 : 15u"
 3 : 30u"
 4 : 50u"
 Housing Color
 0 : Gold Flash
 B : Black

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 32 (SERIES)
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
(B)					
(C)					
(D)					
(E)					

 博 崑 電 子 股 份 有 限 公 司 POWERWAY ELECTRONICS CO.,LTD.		TITLE	RJ45 SIDE ENTRY PCB JACK	UNIT	mm
		圖名		單位	inch
PART NO.	3288-B*1	SCALE	1:1		
料號		比例			
REV.	A.1	DATE	2007-01-12		
版本		日期			
CHECKED BY	Michael	DRAWN BY			
審核		製圖			Valiant