

**Electrical Characteristics :**  
 Insulation Resistance : 500MΩ Min.  
 Contact Resistance : 30mΩ Max.  
 Withstand Voltage : 1000 VAC 1 minute.  
 Current Rating : 1.5A

**Material:**  
 Housing : Thermoplastic UL94V-0  
 Contact : Full Gold Plating  
 Spring Wire : Dia 0.45mm Phosphor Bronze  
 Optional Gold Plating Over Nickel  
 CUL File No : E215573


**PART NO : 5 2 6 6 - B \* 1**

Positions  
 Contacts  
 Ports  
 Gold Plated  
 Housing Color

1 : 8u"  
 2 : 15u"  
 3 : 30u"  
 4 : 50u"

B : Black

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 52 (SERIES)
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
(B)					
(C)					
(D)					
(E)					

 <b>博 崴 電 子 股 份 有 限 公 司</b> <b>POWERWAY ELECTRONICS CO.,LTD.</b>		TITLE	RJ11 6P6C	UNIT	mm
		圖名	SIDE ENTRY PCB JACK	單位	inch
PART NO.	料號	5266-B*1	SCALE	比例	1:1
REV.	版本	A.1	DATE	日期	2007-01-22
CHECKED BY	審核	Michael	DRAWN BY	製圖	Valiant