



Electrical Characteristics :
 Insulation Resistance : 500M Ω Min.
 Contact Resistance : 30m Ω Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 CUL File No : E215573

PART NO : 5 3 6 6 - B * 1

Positions:
 Contacts:
 Ports:
 Gold Plated
 0 : Gold Flash
 1 : 6u"
 2 : 15u"
 3 : 30u"
 4 : 50u"
 Housing Color:
 B : Black

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 53 (SERIES)	TITLE	REV.	DATE	UNIT
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差) : 0.000 mm \pm 0.075 mm 0.00 mm \pm 0.15 mm 0.0 mm \pm 0.25 mm	圖名			mm
(B)						料號			inch
(C)						版本			
(D)						日期			
(E)						日期			
						圖名	RJ11 TOP ENTRY PCB JACK		
						料號	5366-B*1		
						版本			
						日期	2007-05-08		
						日期			
						CHECKED BY	Michael		
						審核			
						DRAWN BY	製圖		
						製圖			
						比例			1:1
						比例			
						Valiant			

PW 博 崙 電 子 股 份 有 限 公 司
 POWERWAY ELECTRONICS CO.,LTD.