


Electrical Characteristics :
 Insulation Resistance : 500MΩ Min.
 Contact Resistance : 50mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A


Material:

Housing: Thermoplastic UL 94V-0
 Contact : Selective Gold Plating
 Terminal: 0.35mm Thickness Phosphor Bronze
 Plated With Gold And Tin In Solder Area.
 CUL File No : E215573

PART NO : 5 3 8 8 C - B * 1



ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 5388C (SERIES)
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	
(B)					TOLERANCE(公差):
(C)					0.000 mm ± 0.075 mm
(D)					0.00 mm ± 0.15 mm
(E)					0.0 mm ± 0.25 mm

 博 崙 電 子 股 份 有 限 公 司 POWERWAY ELECTRONICS CO.,LTD.		TITLE	NON SHIELDED RJ45	UNIT	mm
		圖 名	TOP ENTRY PCB JACK	單位	inch
PART NO.		5388C-B*1	SCALE	1:1	
REV.	A.1	DATE	2007-12-13		
CHECKED BY	Michael	DRAWN BY	David		