


Electrical Characteristics :
 Insulation Resistance : 500M Ω Min.
 Contact Resistance : 50m Ω Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:

Housing: Thermoplastic UL 94V-0
 Contact : Selective Gold Plating
 Terminal: 0.35mm Thickness Phosphor Bronze
 Plated With Gold And Tin In Solder Area.
 CUL File No : E215573

PART NO : 5 3 8 8 C - B*1*



ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 5388C (SERIES)
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	NICK	TOLERANCE(公差): 0.000 mm \pm 0.075 mm 0.00 mm \pm 0.15 mm 0.0 mm \pm 0.25 mm
(B)					
(C)					
(D)					
(E)					



博 崑 電 子 股 份 有 限 公 司
 POWERWAY ELECTRONICS CO.,LTD.

TITLE	SHIELDED RJ45 TOP ENTRY PCB JACK		UNIT	mm
圖 名			單位	inch
PART NO.	5388C-B*1*		SCALE	1:1
料 號			比例	
REV.	A.1	DATE	2007-10-18	
版 本		日期		
CHECKED BY	Michael	DRAWN BY	David	
審 核		製 圖		