



**Electrical Characteristics :**  
 Insulation Resistance : 500MΩ Min.  
 Contact Resistance : 50mΩ Max.  
 Withstand Voltage : 1000 VAC 1 minute.  
 Current Rating : 1.5A

**Material:**  
 Housing: Thermoplastic UL 94V-0  
 Contact : Selective Gold Plating  
 Terminal: 0.35mm Thickness Phosphor Bronze  
 Plated With Gold And Tin In Solder Area.  
 CUL File No : E215573

**PART NO : 5 3 8 8 B - B \* 1**

Positions →  
 Contacts →  
 Ports →  
 Housing Color →

Gold Plated  
 0 : Gold Flash  
 1 : 8u"  
 2 : 15u"  
 3 : 30u"  
 4 : 50u"

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 53 (SERIES)
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差): 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
(B)					
(C)					
(D)					
(E)					

 <b>博 崙 電 子 股 份 有 限 公 司</b> <b>POWERWAY ELECTRONICS CO.,LTD.</b>		TITLE	RJ45 TOP ENTRY PCB JACK	UNIT	mm
		圖名		單位	inch
PART NO.	5388B-B*1	SCALE	1:1		
料號		比例			
REV.	A.1	DATE	2007-02-13		
版本		日期			
CHECKED BY	Michael	DRAWN BY	Valiant		
審核		製圖			