

Electrical Characteristics :
 Insulation Resistance : 500MΩ Min.
 Contact Resistance : 30mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 CUL File No : E215573


PART NO : 6066A-B*2

Positions →
 Contacts →
 Ports →

Gold Plated
 0 : Gold Flash
 1 : 6u"
 2 : 15u"
 3 : 30u"
 4 : 50u"

Housing Color
 B : Black

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 60 (SERIES)
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
(B)					
(C)					
(D)					
(E)					

 博 崑 電 子 股 份 有 限 公 司 POWERWAY ELECTRONICS CO.,LTD.		TITLE	6P6C SIDE ENTRY PCB JACK	UNIT	mm
		圖名		單位	inch
PART NO.		6066A-B*2	SCALE	1:1	
REV.		A.1	DATE	2007-01-29	
料號			日期		
版本			DATE		
CHECKED BY		Michael	DRAWN BY	Valiant	
審核			製圖		