



SUGGESTED PCB LAYOUT
TOP VIEW

Electrical Characteristics :
 Insulation Resistance : 500M Ω Min.
 Contact Resistance : 30m Ω Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 CUL File No : E215573

PART NO : 6166B-B*2

Positions	Ports
Contacts	Gold Plated
Housing Color	0 : Gold Flash
	1 : 6u"
	2 : 15u"
	3 : 30u"
	4 : 50u"
	B : Black

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 61 (SERIES)	TOLERANCE(公差) :
A	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick		0.000 mm \pm 0.075 mm
B						0.00 mm \pm 0.15 mm
C						0.0 mm \pm 0.25 mm
D						
E						



博 崙 電 子 股 份 有 限 公 司
POWERWAY ELECTRONICS CO.,LTD.

TITLE	NON-SHIELDED RJ11	UNIT
圖名	SIDE ENTRY PCB JACK	mm
PART NO.	6166B-B*2	inch
SCALE	1:1	
REV.	A.1	
版本	日期	DATE
2007-07-02		
CHECKED BY	Michael	DRAWN BY
審核		製圖
		Valiant