



Electrical Characteristics :
 Insulation Resistance : 500MΩ Min.
 Contact Resistance : 30mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 CUL File No : E215573

PART NO : 6266-B*2

Positions →
 Contacts →
 Housing Color →

Ports
 Gold Plated
 0 : Gold Flash
 1 : 6u"
 2 : 15u"
 3 : 30u"
 4 : 50u"
 B : Black

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 62 (SERIES)	TITLE	UNIT	
	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差) :	RJ11 SIDE ENTRY PCB JACK	mm	mm
					0.000 mm ± 0.075 mm	PART NO.	inch	inch
					0.00 mm ± 0.15 mm	6266-B*2	SCALE	SCALE
					0.0 mm ± 0.25 mm	REV.	比例	比例
						版本	1:1	1:1
						日期		
						DATE		
						2007-04-30		
						CHECKED BY		
						Michael		
						DRAWN BY		
						製圖		
						Valiant		

PW 博 崑 電 子 股 份 有 限 公 司
 POWERWAY ELECTRONICS CO.,LTD.